

# The Valspar Corporation

## Material Safety Data Sheet

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### Material Identification

**Product ID:** DSL338,339,342  
Product Name: DRI-SLIDE ROBOTICS GREASE LG-03  
Product Use: LUBRICANT  
Print date: 18/Jul/2007  
Revision Date: 26/Feb/2007

#### Company Identification

The Valspar Corporation  
1101 Third Street South  
Minneapolis, MN 55415  
Manufacturer's Phone: 1-612-332-7371

**24-Hour Medical Emergency Phone:** 1-888-345-5732

### 2. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

Common Name CAS-No.	Approx. Weight %	Chemical name
PROPRIETARY OIL	55 - 60	PROPRIETARY OIL
SUPPLIER TRADE SECRET	1 - 5	SUPPLIER TRADE SECRET
SUPPLIER TRADE SECRET	.1 - 1	SUPPLIER TRADE SECRET

If this section is blank there are no hazardous components per OSHA guidelines.

### 3. HAZARDS IDENTIFICATION

#### Primary Routes of Exposure:

Inhalation  
Ingestion  
Skin absorption

#### Emergency Overview:

This section not in use.

**This product contains ingredients that may contribute to the following potential acute health effects:**

#### Inhalation Effects:

Exposure to mists or vapors may cause irritation of the respiratory tract. Inhalation of mist will irritate mucous membranes. If large concentrations of vapors are inhaled, or if the product is processed, sprayed/misted or heated this product can irritate mucous membranes of the upper respiratory tract, with symptoms of sore throat, coughing, and headache.

#### Eye Contact:

Causes severe eye irritation

**Skin Contact:**

May cause dermatitis. May cause skin sensitization.

**Acute Ingestion:**

May be harmful if large amounts are swallowed. May cause pain, nausea, vomiting and diarrhea.

**Other Effects:**

None known

**This product contains ingredients that may contribute to the following potential chronic health effects:**

Prolonged or repeated exposure may cause conjunctivitis. May cause eye damage and pain. Symptoms may include redness, burning, drying and cracking of the skin, and skin burns. Possible sensitization.

See Section 11 for toxicological information about Mutagens, Teratogens and Carcinogens.

If this section is blank, no information is available.

## 4. FIRST AID MEASURES

**Inhalation:**

If inhaled, remove from area to fresh air. Get medical attention if respiratory irritation develops or if breathing becomes difficult. Keep at rest. Move person to fresh air.

**Eye Contact:**

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

**Skin Contact:**

In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. If irritation persists get medical attention. Remove contaminated shoes and discard. Destroy contaminated leather apparel. Remove contaminated clothing and launder before reuse.

**Ingestion:**

If swallowed, get medical attention immediately.

**Medical conditions aggravated by exposure:** Any respiratory or skin condition.

## 5. FIRE FIGHTING MEASURES

Flash point (Fahrenheit):	225° F ( 107° C) TCC/PM
Lower explosive limit:	Not available. %
Upper explosive limit:	Not available. %
Autoignition temperature:	Not available. ° F ( ° C)
Sensitivity to impact:	No.
Sensitivity to static discharge:	Sensitivity to static discharge is not expected.
Hazardous combustion products:	See Section 10.

**Unusual fire and explosion hazards:**

None known.

**Extinguishing media:**

Carbon dioxide, dry chemical, foam and/or water fog.

**Fire fighting procedures:**

Use water spray to cool nearby containers and structures exposed to fire.

## 6. ACCIDENTAL RELEASE MEASURES

## 6. ACCIDENTAL RELEASE MEASURES

### Action to be taken if material is released or spilled:

Avoid contact with eyes.

## 7. HANDLING AND STORAGE

### Precautions to be taken in handling and storage:

Keep container closed when not in use.

## 8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

### Personal Protective Equipment

#### Eye and face protection:

Avoid contact with eyes. Wear chemical goggles if there is the possibility of contact or splashing in the eye.

#### Skin protection:

Appropriate chemical resistant gloves should be worn. To prevent skin contact wear protective clothing covering all exposed areas.

#### Respiratory protection:

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

#### Ventilation

Required when spraying or applying in confined area.

### Exposure Guidelines

#### OSHA Permissible Exposure Limits (PEL's)

#### ACGIH Threshold Limit Value (TLV's)

If this section is blank, no information is available.

## 9. PHYSICAL PROPERTIES

Odor:	Normal for this product type.
Physical State:	Liquid
pH:	Not determined.
Vapor pressure:	1 mmHG @ 68° F ( 20° C)
Vapor density (air = 1.0):	Not determined.
Boiling point:	550° F ( 288° C)
Solubility in water:	Insoluble.
Coefficient of water/oil distribution:	Not determined.
Density (lbs per US gallon):	7.6
Specific Gravity:	.91
Evaporation rate (butyl acetate = 1.0):	Not determined.

## 10. STABILITY AND REACTIVITY

Stability:	Stable
Conditions to Avoid:	None known.
Incompatibility:	None known.
Hazardous Polymerization:	None anticipated.
Hazardous Decomposition Products:	Carbon monoxide and carbon dioxide.

## 10. STABILITY AND REACTIVITY

Sensitivity to static discharge:

Sensitivity to static discharge is not expected.

## 11. TOXICOLOGICAL INFORMATION

Mutagens:

Teratogens:

Carcinogens:

If this section is blank, no information is available.

## 12. ECOLOGICAL DATA

Not available at this time.

## 13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

## 14. TRANSPORTATION INFORMATION

### U.S. Department of Transportation

Proper Shipping Name: LUBRICANT, NOT REGULATED

UN ID Number: NRLUBE

### U.S. Highway & Rail Shipments

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

### International Air Transport Association:

Proper Shipping Name: LUBRICANT, NOT REGULATED

UN ID Number: NRLUBE

### International Maritime Organization:

Proper Shipping Name: LUBRICANT, NOT REGULATED

Non-Bulk UN ID Number: NRLUBE

## 15. REGULATORY INFORMATION

### U.S. FEDERAL REGULATIONS:

Common Name CAS-No.	Approx. Weight %	SARA 302	SARA 313	CERCLA RQ in lbs.
SUPPLIER TRADE SECRET	.1 - 1		YES	

### SARA 311/312 Hazard Class:

Acute: Yes

Chronic: Yes

Flammability: No  
Reactivity: No  
Sudden Pressure: No

## U.S. STATE REGULATIONS:

### Pennsylvania Right To Know:

PROPRIETARY OIL Trade Secret  
SUPPLIER TRADE SECRET Trade Secret

### Additional Non-Hazardous Materials

HYDROTREATED PARAFFINIC BASE OIL 64742-58-1  
PROPRIETARY RESIN Trade Secret

### California Proposition 65:

WARNING: This product contains a chemical known to the State of California to cause cancer.

**Rule 66 status of product** Not photochemically reactive.

## INTERNATIONAL REGULATIONS - Chemical Inventories

**TSCA Inventory:** All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

**Canada Domestic Substances List:** All components of this product are listed on the Domestic Substances List.

## 16. OTHER INFORMATION

### HMIS Codes

**Health:** 1  
**Flammability:** 1  
**Reactivity:** 0  
**PPE:** X - See Section 8 for Personal Protective Equipment (PPE).

### Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

### Disclaimer:

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.