

1. Identification of the substance/preparation and company/undertaking

Product name	Longtime PD 0
SDS no.	451388
Historic SDS no.	DE-08222, AT-451388, BE-451388, BG-451388, CZ-508222, DK-451388, EE-8222, ES-451388, FI-451388, FR-451388, GR-451388, HU-08222, IT-08222, LT-8222, NL-451388, NO-558033, PL-8222, RU-8222, SI-8222, SE-558033, SK-8222, TR-451388, UK-3702, US-62000-AG
Use of the substance/preparation	Lubricant For specific application advice see appropriate Technical Data Sheet or consult our company representative.
Supplier	Nordic Lubricants AB Castrol Industrial Lubricants and Services Box 49104 S-100 28 Stockholm Sweden Tel.: +46 (0)8-441 11 00 Fax: +46 (0)8-651 01 35 Carechem: +44 (0) 208 762 8322
EMERGENCY TELEPHONE NUMBER	Carechem: +44 (0) 208 762 8322
E-mail address	MSDSadvice@bp.com

2. Hazards identification

This preparation is classified as dangerous according to Directive 1999/45/EC as amended and adapted.

Physical/chemical hazards	Not applicable.
Human health hazards	May cause sensitisation by skin contact.
Environmental hazards	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Additional hazards	Note: High Pressure Applications Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. See 'Notes to physician' under First-Aid Measures, Section 4 of this Safety Data Sheet.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

3. Composition/information on ingredients

Highly refined mineral oil and additives. Thickening agent.

Chemical name	CAS no.	%	EINECS / ELINCS.	Classification
Base oil - unspecified	Varies	20 - 50		Not classified. [2]
Base oil - unspecified	64742-52-5	20 - 50	265-155-0	Not classified. [2]
Base oil - unspecified	Proprietary	1 - 5		Not classified. [2]
Reaction product of ammonium molybdate and C12-C24-diethoxylated alkylamine (1:5-1:3)	Proprietary	1 - 5	412-780-3	Xi; R38 R43 N; R51/53 [1]
Phosphorous acid, decyl diphenyl ester.	26544-23-0	0.1 - 1	247-777-4	Xi; R38 R43 N; R51/53 [1]
Zinc alkyl dithiophosphate	68649-42-3	0.1 - 1	272-028-3	Xi; R41 N; R51/53 [1]

See section 16 for the full text of the R-phrases declared above

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] PBT-substance

[4] vPvB-substance

Occupational exposure limits, if available, are listed in section 8.

Product name	Longtime PD 0	Product code	451388-DE03	Page:	1/5
Version	2	Date of issue	20 June 2008	Format Sweden	Language ENGLISH
			(Sweden)		(ENGLISH)

4 . First-aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.
Skin contact	Immediately wash exposed skin with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms appear.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If potentially dangerous quantities of this material have been swallowed, call a physician immediately.
Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects. Note: High Pressure Applications Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue becomes swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimise tissue loss and prevent or limit permanent damage. Note that high pressure may force the product considerable distances along tissue planes.

5 . Fire-fighting measures

Extinguishing media	
Suitable	In case of fire, use water fog, foam, dry chemical or carbon dioxide extinguisher or spray. This material is harmful to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Not suitable	Do not use water jet.
Hazardous decomposition products	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides
Unusual fire/explosion hazards	This material is not explosive as defined by established regulatory criteria.
Special fire-fighting procedures	None identified.
Protection of fire-fighters	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

6 . Accidental release measures

Personal precautions	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).
Environmental precautions	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material.
Large spill	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see section 1 for emergency contact information and section 13 for waste disposal.
Small spill	Stop leak if without risk. Move containers from spill area. Use a tool to scoop up solid or absorbed material and place into appropriate labelled waste container. Dispose of via a licensed waste disposal contractor.

7 . Handling and storage

Handling	Do not get on skin or clothing. Avoid contact of spilt material and runoff with soil and surface waterways. Wash thoroughly after handling.
Storage	Keep container tightly closed. Keep container in a cool, well-ventilated area.

8 . Exposure controls/personal protection

Ingredient name
Base oil - unspecified

Occupational exposure limits

Hyg gränsvärden enligt gällande AFS (Sweden).

KTV: 3 mg/m³ 15 minute(s). Form: Oil mist, including oil fumes

NGV: 1 mg/m³ 8 hour(s). Form: Oil mist, including oil fumes

ACGIH TLVs

Product name Longtime PD 0

Product code 451388-DE03

Page: 2/5

Version 2

Date of issue 20 June 2008

Format Sweden

Language ENGLISH

(Sweden)

(ENGLISH)

For information and guidance, the ACGIH values are included. For further information on these please consult your supplier.

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Exposure controls

Occupational exposure controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective occupational exposure limits.
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Personal protective equipment

Respiratory protection	None required. However, use of adequate ventilation is good industrial practice.
Hand protection	<p>Wear suitable gloves. Chemical-resistant gloves. Recommended: Nitrile gloves.</p> <p>The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.</p>
Eye protection	Safety glasses with side shields.
Skin and body	Do not get on skin or clothing. Wear suitable protective clothing.

9. Physical and chemical properties

General information

Appearance

Physical state	Grease
Colour	Brown. [Dark]
Odour	Mild.

Important health, safety and environmental information

Flash point	Closed cup: >150°C (>302°F)
Vapour pressure	<0.01 kPa (<0.075 mm Hg) at 20°C
Drop Point	194 °C
Density	<1000 kg/m ³ (<1 g/cm ³) at 20°C
Solubility	Insoluble in water.

10. Stability and reactivity

Stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	No specific data.
Materials to avoid	Reactive or incompatible with the following materials: oxidizing materials.
Hazardous decomposition products	<p>Combustion products may include the following:</p> <ul style="list-style-type: none"> carbon oxides nitrogen oxides sulfur oxides metal oxide/oxides <p>Under normal conditions of storage and use, hazardous decomposition products should not be produced.</p>

11. Toxicological information

Chronic toxicity

Chronic effects	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
------------------------	--

Effects and symptoms

Eyes	May cause eye irritation.
Skin	<p>May cause severe allergic skin reaction.</p> <p>Note: High Pressure Applications</p> <p>Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency.</p> <p>See 'Notes to physician' under First-Aid Measures, Section 4 of this Safety Data Sheet.</p>
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.

12 . Ecological information

Persistence/degradability	Inherently biodegradable
Mobility	Non-volatile. Grease. insoluble in water.
Environmental hazards	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13 . Disposal considerations

Disposal considerations / Waste information	The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
Unused product	
European waste catalogue (EWC)	01 12* spent waxes and fats However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.
Packaging	
European waste catalogue (EWC)	01 10* packaging containing residues of or contaminated by dangerous substances
Methods of disposal	The regulations regarding manufacturers' responsibility for packaging material waste is regulated in "Förordningen om producentansvar för förpackningar". Packaging materials are to be reused or recycled in accordance with the goals outlined in this regulation. The company complies with this manufacturer's responsibility through its association with REPA, which is a subsidiary company of four materials handling companies. The materials handling companies collect, remove and process used and sorted packaging materials through the employment of contractors. Questions regarding collection of packaging materials on a local basis may be directed to the materials company and its contractors. For further information, contact REPA, www.repa.se . Emptying instructions for steel drums: Scrape the drum very clean and send to an authorized recycler.

14 . Transport information

Not classified as hazardous for transport (ADR/RID, ADNR, IMDG, ICAO/IATA)

15 . Regulatory information

Classification and labelling have been performed according to EU directives 1999/45/EC and 67/548/EEC as amended and adapted.

Label requirements

Hazard symbol or symbols



Irritant



Indication of danger

Risk phrases

R43- May cause sensitisation by skin contact.
R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases

S28- After contact with skin, wash immediately with plenty of soap and water.
S36/37/39- Wear suitable protective clothing, gloves and eye/face protection.
S61- Avoid release to the environment. Refer to special instructions/safety data sheet.

Contains

Reaction product of ammonium molybdate and C12-C24-diethoxylated alkylamine (1:5-1:3)

Other regulations

Europe inventory

At least one component is not listed in EINECS but all such components are listed in ELINCS. Please contact your supplier for information on the inventory status of this material.

United States inventory (TSCA 8b)

All components are listed or exempted.

Australia inventory (AICS)

At least one component is not listed.

Canada inventory

At least one component is not listed.

China inventory (IECSC)

All components are listed or exempted.

Japan inventory (ENCS)

At least one component is not listed.

Korea inventory (KECI)

All components are listed or exempted.



Product name Longtime PD 0

Product code 451388-DE03

Page: 4/5

Version 2

Date of issue 20 June 2008

Format Sweden

Language ENGLISH

(Sweden)

(ENGLISH)

16 . Other information

Full text of R-phrases referred to in sections 2 and 3

R41- Risk of serious damage to eyes.
R38- Irritating to skin.
R43- May cause sensitisation by skin contact.
R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

History

Date of issue/ Date of revision

20/06/2008.

Date of previous issue

19/06/2006.

Prepared by

Product Stewardship Group

Notice to reader

Indicates information that has changed from previously issued version.

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from us.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken.